

PREPARATION AND APPLICATION PROCEDURE

GALVANIZED OR PAINTED STEEL (SHEET)

PREPARATION SEALANT FINISH Procedure: Procedure: Procedure: - Rinse the surface well with a 2000 lb. pressure washer. - In warm weather dilute with - To obtain a surface that will remain beautiful for a - Apply and scrub the **TexNov Surface Preparer**. water (50 ml/liter) for ease of long time, apply *TexNov Met-30* Sealant or TexNov - Let act for 15 minutes by keeping the surface wet. WRS-40 Sealant for horizontal surfaces. Use a application. The temperature of - Rinse thoroughly with a pressure washer. the surface should not exceed 30° brush or a roller with 10 mm bristles or a sprayer. - Let the surface dry for 24 hours prior to applying the C at the application. - Let the surface dry for 24 hours. - Apply 2 coats of TexNov Acrylic finish coating. Coating. Use a brush or roller Note: In places where there is rust, apply a primer to metal with 10 mm bristles (24 hours previously. between applying each coat). - Let the surface dry for 24 hours.

Maintenance: Clean the surface with TexNov Surface Preparer (6 water / 1 Preparer). Let dry and add a coat of Met-30 Sealant every 3 years or as needed.

This should enable you to keep your surface in good condition.

