SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

PRODUCT	COMPANY IDENTIFICATION
Name: TexPro FlexStop CB **Description:** Adhesive and waterproofing. **Restriction of use:** Sanding or grinding the dried product emits dangerous dust.	**TexNov inc.** 839 Joseph-Louis-Mathieu Sherbrooke, Québec, Canada J1R 0X3 **Emergency Phone Number:** 1 877 316-6388

SECTION 2 - HAZARD IDENTIFICATION

Pictograms

Warning statements

DANGER

Product classification

Specific target organ toxicity - repeated exposure - Category 1

Hazard statements

Causes damage to organs (liver, spleen, kidneys, lymph node) after repeated exposure or prolonged exposure.

Precautionary statements

Prevention: Do not breathe dust / fume / gas / mist / vapors / spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when handling this product.

Wear gloves and safety glasses. Use in a well-ventilated area. Inhalation of sanding dust or grinding of the dry product may be harmful. These dusts can cause irritation to the respiratory tract and can damage organs (lungs). This product contains ingredients that are considered carcinogenic if transformed into dust.

Intervention: Consult a doctor if you feel unwell.

INGESTION: Call Poison Control Center or doctor immediately. Do not induce vomiting unless advised by the doctor. EYES: Immediately flush with plenty of water for 15 minutes, occasionally lifting the eyelids. SKIN: wash with soap and water. Take off immediately all contaminated clothing. INHALATION: If person is not breathing, give artificial respiration and seek medical attention. If breathing is difficult, remove victim to fresh air.

STORAGE: Store at 5 to 30°C in a closed plastic container. Keep away from frost.

DISPOSAL: Dispose of contents and container in accordance with local regulations.

SECTION 3 - COMPOSITION / INFORMATION ON THE COMPONENTS

Ingredient	CAS number	% (weight/weight)
Crystalline silica (Quartz)	14808-60-7	15 - 40

The Crystalline silica (Quartz) content of the product is considered encapsulated or embedded in the binder polymer and not bio-accessible by inhalation in normal use of the product. Based on current knowledge and applicable concentrations, there are no other ingredients in this product that are classified as hazardous by GHS and that should be reported in this section.

The application instructions and performance characteristics are based on information we believe to be reliable. They are offered to the best of our knowledge, but without guarantee, as conditions and methods of use of our products are beyond our control.

SECTION 4 - FIRST AIDS

Eye contact: Flush eyes with water. Consult a physician if irritation persists.
Skin contact: Soap and rinse exposed area thoroughly. Consult a physician if irritation persists.
Ingestion: Rinse mouth with water. Do not induce vomiting unless prompted by medical advice. Do not swallow anything to an unconscious person.
Inhalation: Move the person to a well-ventilated area. Consult a doctor if headaches persist.

SECTION 5 - MESURE IN CASE OF FIRE

Non-flammable product, but it may splash if heated above boiling point.
Combustion product: If the product is heated to combustion, after the release of water vapor, carbon oxides will be emitted.
Use the appropriate extinguisher.

SECTION 6 - MEASURES TO BE TAKEN IN CASE OF ACCIDENTAL DISPERSION

Pick up all the dispersion with a shovel and eliminate the discards. Do not send the dispersion into the sewer, occurs can clog the piping.

SECTION 7 - HANDLING AND STORAGE

Handling safety precaution: Do not eat, smoke or drink in the work area. Wash hands after handling. Avoid contact with hands and eyes.
Storage safety conditions: Keep in a dry place away from frost and sunlight. The product may coagulate. The storage temperature is 5 to 30°C. Keep in a closed plastic container.

SECTION 8 - EXPOSURE CONTROL / PERSONAL PROTECTION

CONTROL PARAMETERS:
Occupational Exposure Limits: Sanding or grinding this product in its dry form may produce particles of crystalline silica.

Breathable dust	RSST		ACGIH TLV	
Ingredient	**VEMP**	**DIVS**	**TWA**	**STEL**
Crystalline silica (Quartz)	0.1 mg/m^3	50 mg/m^3	0.025mg/m^3	Not available

RSST : Regulation respecting occupational health and safety; VEMP : Weighted average exposure value
DIVS : Immediate danger to life and health; ACGIH : American Conference of Governmental Industrial Hygienists
TLV : Threshold limit value; TWA : Time-weighted average; STEL : Short-terrm exposure limit

Individual protection measures
Respiratory protection: Wear appropriate respiratory protection if dusts / fumes / gases / mists / vapors / aerosols are possible above permissible limits. Use in a well ventilated place.
Eye Protection: To reduce exposure, wear safety glasses.
Hand protection: To reduce exposure, wear gloves. Wash your hands thoroughly after using the product. Do not eat, drink or smoke when handling this product.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Creamy with a slight blue color.
Odor: Low odor of ammonia.
Odor threshold: Not available
pH: 8.5-9.
Freezing point: 0°C
Boiling point: 100°C.

The application instructions and performance characteristics are based on information we believe to be reliable. They are offered to the best of our knowledge, but without guarantee, as conditions and methods of use of our products are beyond our control.

Evaporation rate: Not available.
Flammability (solid and gas): Not applicable.
Explosive limit: Not applicable.
Vapor pressure: Not available.
Vapor density: Not available.
Relative density: 1,45.
Solubility in water: may be diluted with water.
Partition coefficient n-octanol / water: Not available.
Auto-ignition temperature: Not applicable.
Decomposition temperature: Not available.
Viscosity: 17200 mm^2/s (converted from measurement on Brookfield).

SECTION 10 - STABILITY AND REACTIVITY

Chemical stability: This product is considered stable under recommended storage conditions.
Reactivity: Incompatible with strong oxidants and strong acids.
Possibility of hazardous reactions: This product can not polymerize.
Hazardous decomposition product: If the product is heated to combustion, there will be emission of carbon oxides.

SECTION 11 - TOXICOLOGICAL DATA

Routes of entry: This product may be absorbed through the respiratory, digestive and cutaneous routes.
Acute toxicity (calculated GHS):

Product	DL_{50} oral, mg/kg	DL_{50} cutaneous, mg/kg	CL_{50}, mg/L
TexPro FlexStop CB	> 10000 (rat)	> 10000 (rabbit)	> 100 (rat)

Skin irritation: Virtually nil. An irritation of a mechanical nature is possible.
Irritation of the eyes: Not important. An irritation of a mechanical nature is possible.
Respiratory or skin sensitization: Virtually nil.
Specific target organ toxicity: Causes damage to organs (liver, spleen, kidneys, and lymph node) after repeated exposure or prolonged exposure.
Extract from the toxicological index linked to this mention: A very small proportion of silica can pass into the bloodstream in the form of silicic acid. The latter can be deposited in the liver, spleen and lymph nodes. The silicic acid is then excreted unchanged via the kidneys.
Carcinogenicity:
The sanding or grinding of this product is its dry form can produce particles of crystalline silica which are considered carcinogen classified 1 according to IARC. Repeated inhalation of crystalline silica can cause lung damage and silicosis.

Ingredient	CIRC	ACGIH	NTP
Crystalline silica (Quartz)	Group 1	Group A2	K

CIRC : International Center for Research on Cancer. Group 2B : May be carcinogenic to humans. Group A4 : Non-classifiable substance as a carcinogen to humans. NTP : National Toxicology Program; N : Negative.

Reproductive toxicity: none.
Germ cell mutagenicity: none.

SECTION 12 - ECOLOGICAL DATA

Ecotoxicology: Not available.
Bioaccumulative potential: Not available.
Volatile organic compounds (V.O.C.): ≤ 50g / L.

The application instructions and performance characteristics are based on information we believe to be reliable. They are offered to the best of our knowledge, but without guarantee, as conditions and methods of use of our products are beyond our control.

SECTION 13 - DATA FOR DISPOSAL OF THE PRODUCT

Dispose of releases in according to Municipal, Provincial and National Regulations.

SECTION 14 - TRANSPORT INFORMATION

Shipping Name: Not Applicable.
TDG Classification : Not Regulated.

SECTION 15 - REGULATORY INFORMATION

WHMIS 2015 Classification: Specific target organ toxicity, repeated exposure, Category 1
The product classification and SDS have been developed in accordance with the HPR.

SECTION 16 - OTHER INFORMATION

SDS prepared by: TexNov inc.
Emergency telephone number: 1-800-688-5990
Revision Date: 2023-07-01
Warning: The information and recommendations contained in this document have been written to the best of knowledge and technical data collected by TexNov inc. at the time of the revision. This document is intended to inform users of the product about the precautionary measures when using the product. No warranty is given on the properties mentioned on the products. No liability will be assumed for cases of misuse of the product or failure to observe the safety instructions contained in this document.

839 Joseph-Louis-Mathieu, Sherbrooke J1R 0X3
www.texnov.com - info@texnov.com
1 877 316-6388
The application instructions and performance characteristics are based on information we believe to be reliable. They are offered to the best of our knowledge, but without guarantee, as conditions and methods of use of our products are beyond our control.